

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

## **Glued laminated timber (glulam)**

according to the product specification listed in the current addendum to this certificate placed on the market by

### **Company**

**RUBNER HOLZINDUSTRIE GES.M.B.H.**

**Obere Hauptstraße 18**

**AT-8234 Rohrbach an der Lafnitz**

and produced in the manufacturing plant

**AT-8234 Rohrbach an der Lafnitz, Obere Hauptstraße 18**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

### **EN 14080:2013**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

**Certificate number:** 1359-CPR-0611

**Date of first issue:** 10.04.2015


**Date of issuance:** 17.02.2020

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see [www.holzforchung.at](http://www.holzforchung.at).



**Dr. Andreas Neumüller**  
Authorised signatory



**Dr. Manfred Brandstätter**  
Head of the Certification Body

# Addendum to certificate 1359-CPR-0611

Date of issue: 17.02.2020

## Scope of certification for the following products:

### GLUED LAMINATED TIMBER (GLULAM)

Timber species/ strength classes:	PCAB - spruce; ABAL - fir: GL 22h, GL 24h, GL 28h, GL 30h
Mechanical resistance:	according to EN 14080
Service classes:	1, 2
Adhesive:	
- Finger joints	Type I: EPI according to EN 16254
- Surface bonding	Type I: EPI according to EN 16254
Reaction to fire:	D-s2, d0
Formaldehyde class:	E1
Natural durability class:	according to EN 350-2