

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

Glued laminated timber (glulam)

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

RUBNER HOLZINDUSTRIE GES.M.B.H.

Obere Hauptstraße 18 AT-8234 Rohrbach an der Lafnitz

and produced in the manufacturing plant

AT-8234 Rohrbach an der Lafnitz, Obere Hauptstraße 18

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14080:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0611 Date of first issue: 10.04.2015 Date of issuance: 04.05.2023

This certificate will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

Dipl.-Ing. Bernhard Kraus

Authorised signatory

4 Grad

Dr. Manfred Brandstätter Head of the Certification Body

Addendum to certificate 1359-CPR-0611

Date of issue: 04.05.2023



Scope of certification for the following products:

GLUED LAMINATED TIMBER (GLULAM)

Timber species/ strength classes:

PCAB - Spruce; ABAL - Fir:

GL 22h, GL 24h, GL 28h, GL 30h

PNSY - Pine: GL 24h

according to EN 14080:2013

1, 2

Service classes:

Adhesive:

- Finger joints

- Surface bonding

Mechanical resistance:

Reaction to fire:

Formaldehyde class:

Natural durability class:

Type I: EPI according to EN 16254

Type I: EPI according to EN 16254

D-s2, d0

E1

according to EN 350-2